

# Topside Tensioners



Integrated Solutions  
to Piping Problems



			Load Capacity		Hydraulic Pressure Area		A	B	C A/F	D	
SRT 1	1"	M24	28.1	280	2.89	1867	87	117	68	175	175
	1 1/8"							120	72	181	178
SRT 2	1"	M24	46	450	4.65	3001	103	117	75	175	175
		M27						120	80	181	178
	1 1/8"	M30						120	80	181	184
	1 1/4"	M33						123	84	188	190
	M36	126	89	195	196						
SRT 3	1 1/4"	M33	66.2	660	6.82	4401	118	123	88	190	192
	1 3/8"	M36						126	96	197	198
	1 1/2"	M39						130	96	203	204
	1 5/8"	M48						133	105	209	211
SRT 4	1 1/2"	M39	101.4	1000	10.34	6668	140.5	132	112	211	212
	1 5/8"	M42						135	114	217	218
	1 3/4"	M45						139	118	223	225
	1 7/8"	M48						142	114	230	231
	2"							145	120	236	
SRT 5	2"	M52	150.5	1500	15.5	10003	175.5	148	120	246	248
	2 1/4"	M56						154	138	259	258
		M60						161	138		262
	2 1/2"	M64						161	153	272	273
	2 3/4"	M68						167	156	284	283
SRT 6	2 3/4"	M72	250.9	2500	25.84	16671	219	167	157	294	297
	3"	M76						174	182	307	308
		M80						180	190		312
	3 1/4"	M85						180	190	320	323
	3 1/2"	M90						186	205	332	334

